



# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Propane substance with national workplace exposure limit(s) (BE) (Note U)	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5	20 - 50	Flam. Gas 1, H220
Butane substance with national workplace exposure limit(s) (GB, HU) (Note C)(Note U)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	20 - 50	Flam. Gas 1, H220
Ethanol substance with national workplace exposure limit(s) (BE, FR, GB, HU, IT, NL, PT)	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5 (REACH-no) 01-2119457610-43	20 - 50	Flam. Liq. 2, H225
Benzyl Salicylate	(CAS No) 118-58-1 (EC no) 204-262-9	< 1	Skin Sens. 1, H317
Benzyl Acetate substance with national workplace exposure limit(s) (BE, IT, PT)	(CAS No) 140-11-4 (EC no) 205-399-7	< 1	Not classified
Butylphenyl Methylpropional	(CAS No) 80-54-6 (EC no) 201-289-8 (REACH-no) 01-2119485965-18	< 1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Chronic 2, H411
Hexyl Cinnamal	(CAS No) 101-86-0 (EC no) 202-983-3 (REACH-no) 01-2119533092-50	< 1	Skin Sens. 1, H317
Eugenol	(CAS No) 97-53-0 (EC no) 202-589-1	< 1	Eye Irrit. 2, H319 Skin Sens. 1, H317
Sodium Benzoate substance with national workplace exposure limit(s) (BE, FR, GB)	(CAS No) 532-32-1 (EC no) 208-534-8 (REACH-no) 01-2119460683-35	< 1	Not classified
Triethanolamine substance with national workplace exposure limit(s) (BE, IT, NL, PT)	(CAS No) 102-71-6 (EC no) 203-049-8 (REACH-no) 01-2119486482-31	< 1	Not classified
IsoButane substance with national workplace exposure limit(s) (BE, IT, PT) (Note C)(Note U)	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0	< 1	Flam. Gas 1, H220
Diethyl Phthalate substance with national workplace exposure limit(s) (BE, FR, GB, IT, PT)	(CAS No) 84-66-2 (EC no) 201-550-6	< 1	Not classified
Diphenylether substance with national workplace exposure limit(s) (BE, FR, GB, IT, PT)	(CAS No) 101-84-8 (EC no) 202-981-2	< 1	Eye Irrit. 2, H319 Aquatic Chronic 2, H411

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U : When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Water spray. Foam.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Recover mechanically the product.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.  
Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Diphenylether (101-84-8)		
United Kingdom	Local name	Diphenyl ether
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	7.1 mg/m <sup>3</sup> Diphenyl ether (vapour); United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	1 ppm Diphenyl ether (vapour); United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
Diethyl Phthalate (84-66-2)		
United Kingdom	Local name	Diethyl phthalate
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> Diethyl phthalate; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> Diethyl phthalate; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Ethanol (64-17-5)</b>		
United Kingdom	Local name	Ethanol
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	1000 ppm
<b>Sodium Benzoate (532-32-1)</b>		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup> Inhalable dust; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005); Respirable dust; 10 mg/m <sup>3</sup> ; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
<b>Butane (106-97-8)</b>		
United Kingdom	Local name	Butane
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	1450 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1810 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage. See paragraphs 49–51), (only applies if Butane contains more than 0.1% of buta-1,3-diene)

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Gas.
Colour	: No data available
Odour	: Fresh.
Odour threshold	: No data available
pH	: 6.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -11.5 °C
Boiling point	: < 100 °C
Flash point	: No data available
Auto-ignition temperature	: 350 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapour pressure	: 77 psia
Relative vapour density at 20 °C	: No data available
Relative density	: < 1 (water=1)
Solubility	: Soluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Explosive limits : 3.3 - 19 vol %  
27 vol %  
3.4 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Contains gas under pressure; may explode if heated.

### 10.3. Possibility of hazardous reactions

Heating may cause a fire or explosion.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified (Lack of data)

<b>Diphenylether (101-84-8)</b>	
LD50 oral rat	3370 mg/kg (Rat)
LD50 dermal rat	4000 mg/kg (Rat)
LD50 dermal rabbit	> 7940 mg/kg (Rabbit)
<b>Hexyl Cinnamal (101-86-0)</b>	
LD50 oral rat	3100 mg/kg (Rat)
LD50 oral	> 2450 mg/kg bodyweight
LD50 dermal rabbit	> 3000 mg/kg (Rabbit)
LD50 dermal	> 3000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5000 mg/l/4h
<b>Butylphenyl Methylpropional (80-54-6)</b>	
LD50 oral rat	1390 mg/kg (Rat)
LD50 oral	1390 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit)
LD50 dermal	> 5000 mg/kg bodyweight
<b>Benzyl Acetate (140-11-4)</b>	
LD50 oral rat	2490 mg/kg (Rat)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit)
<b>Benzyl Salicylate (118-58-1)</b>	
LD50 oral rat	2227 mg/kg (Rat)
LD50 dermal rabbit	14150 mg/kg (Rabbit)
<b>Eugenol (97-53-0)</b>	
LD50 oral rat	2680 mg/kg (Rat)
LD50 oral	1930 mg/kg bodyweight
LD50 dermal	> 2000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 2580 mg/l/4h
<b>Diethyl Phthalate (84-66-2)</b>	
LD50 oral rat	8600 mg/kg (Rat)
LD50 dermal rabbit	> 7940 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat)
<b>Ethanol (64-17-5)</b>	
LD50 oral rat	10740 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Ethanol (64-17-5)</b>	
LD50 oral	10470 mg/kg bodyweight
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
LD50 dermal	15800 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 99999 mg/l/4h

<b>Sodium Benzoate (532-32-1)</b>	
LD50 oral rat	> 2700 mg/kg (Rat)
LD50 oral	2100 mg/kg bodyweight
LD50 dermal rat	> 7940 mg/kg (Rat)
LD50 dermal rabbit	2000 mg/kg (Rabbit)

<b>Triethanolamine (102-71-6)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; 6400 mg/kg bodyweight; Rat)
LD50 oral	8000 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit)
LD50 dermal	> 10000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 1.8 mg/m <sup>3</sup>

Skin corrosion/irritation : Not classified (Lack of data)  
pH: 6.5

Serious eye damage/irritation : Not classified (Lack of data)  
pH: 6.5

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified (Lack of data)

Carcinogenicity : Not classified (Lack of data)

Reproductive toxicity : Not classified (Lack of data)

Specific target organ toxicity (single exposure) : Not classified (Lack of data)

Specific target organ toxicity (repeated exposure) : Not classified (Lack of data)

Aspiration hazard : Not classified (Lack of data)

<b>250ML AIR FRESHENER REFILL - FRESH LINEN</b>	
Vaporizer	Aerosol

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>Diphenylether (101-84-8)</b>	
LC50 fish 1	1.7 mg/l (LC50; 96 h; Lepomis macrochirus)
EC50 Daphnia 1	0.68 mg/l (EC50; 48 h)
Threshold limit algae 1	1.7 mg/l (EC50; 96 h)

<b>Hexyl Cinnamal (101-86-0)</b>	
LC50 fish 1	1.7 mg/l
EC50 other aquatic organisms 2	> 0.32 mg/l IC50 algae (72 h) mg/l

<b>Butylphenyl Methylpropional (80-54-6)</b>	
LC50 fish 1	> mg/l >2.2/4.6,LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio
EC50 Daphnia 1	10.7 mg/l (EC50; 48 h)
EC50 other aquatic organisms 1	10.7 mg/l EC50 waterflea (48 h)

<b>Benzyl Acetate (140-11-4)</b>	
LC50 fish 1	68 mg/l (LC50; 96 h)

<b>Eugenol (97-53-0)</b>	
LC50 fish 1	24 mg/l (LC50; 96 h)
EC50 other aquatic organisms 1	1.9 mg/l EC50 waterflea (48 h)
EC50 other aquatic organisms 2	15.4 mg/l IC50 algae (72 h) mg/l

<b>Diethyl Phthalate (84-66-2)</b>	
LC50 fish 2	17 ppm (LC50; 96 h; Pimephales promelas)

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Diethyl Phthalate (84-66-2)</b>	
EC50 Daphnia 2	52 mg/l (EC50; 48 h)
<b>Ethanol (64-17-5)</b>	
LC50 fish 1	14200 mg/l
EC50 other aquatic organisms 1	5012 mg/l EC50 waterflea (48 h)
EC50 other aquatic organisms 2	275 mg/l IC50 algea (72 h) mg/l
<b>Sodium Benzoate (532-32-1)</b>	
LC50 fish 1	> 100 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 1	< 650 mg/l (EC50; 48 h)
EC50 Daphnia 2	> 100 mg/l (EC50; 48 h)
EC50 other aquatic organisms 1	> 100 mg/l EC50 waterflea (48 h)
EC50 other aquatic organisms 2	30.5 mg/l IC50 algea (72 h) mg/l
<b>Propane (74-98-6)</b>	
Threshold limit algae 2	8 mg/l (IC50; 72 h; Algae)
<b>Triethanolamine (102-71-6)</b>	
LC50 fish 1	11800 mg/l
LC50 fish 2	450 - 1000 mg/l (LC50; 96 h; Lepomis macrochirus)
EC50 other aquatic organisms 1	2038 mg/l EC50 waterflea (48 h)
EC50 other aquatic organisms 2	216 mg/l IC50 algea (72 h) mg/l
<b>IsoButane (75-28-5)</b>	
LC50 fish 1	9.89 mg/l (LC50; 96 h; Pimephales promelas)
LC50 fish 2	27.98 mg/l (LC50; Other; 96 h; Pisces; Fresh water)
EC50 Daphnia 1	10.67 mg/l (LC50; 48 h; Daphnia magna)
EC50 Daphnia 2	16.33 mg/l (LC50; 48 h; Daphnia sp.)
Threshold limit algae 2	7.15 mg/l (EC50; 72 h; Algae)

### 12.2. Persistence and degradability

<b>Diphenylether (101-84-8)</b>	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.
Biochemical oxygen demand (BOD)	1.68 - 2.0 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.19 - 2.5 g O <sub>2</sub> /g substance
ThOD	2.63 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.72
<b>Hexyl Cinnamal (101-86-0)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>Butylphenyl Methylpropional (80-54-6)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>Benzyl Acetate (140-11-4)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>Benzyl Salicylate (118-58-1)</b>	
Persistence and degradability	Biodegradability in water: no data available.
<b>Eugenol (97-53-0)</b>	
Persistence and degradability	Biodegradability in water: no data available.
<b>Diethyl Phthalate (84-66-2)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air.
<b>Ethanol (64-17-5)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.70 g O <sub>2</sub> /g substance
ThOD	2.10 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.43
<b>Sodium Benzoate (532-32-1)</b>	
Persistence and degradability	Readily biodegradable in water.

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
<b>Triethanolamine (102-71-6)</b>	
Persistence and degradability	Readily biodegradable in water. Highly mobile in soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	0.02 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.50 g O <sub>2</sub> /g substance
ThOD	2.04 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.02
<b>IsoButane (75-28-5)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Not applicable (gas).
<b>12.3. Bioaccumulative potential</b>	
<b>Diphenylether (101-84-8)</b>	
BCF fish 1	49 - 594 (BCF)
BCF fish 2	195 - 470 (BCF; 168 h)
Log Pow	4.20
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
<b>Hexyl Cinnamal (101-86-0)</b>	
BCF other aquatic organisms 1	3120 (BCF)
Log Pow	4.7
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
<b>Butylphenyl Methylpropional (80-54-6)</b>	
Log Pow	4.3
<b>Benzyl Acetate (140-11-4)</b>	
Log Pow	1.96 - 2.0 (QSAR)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Benzyl Salicylate (118-58-1)</b>	
Log Pow	4.31 (Estimated value)
<b>Eugenol (97-53-0)</b>	
Log Pow	2.27
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Diethyl Phthalate (84-66-2)</b>	
BCF fish 1	15 - 16 (BCF)
BCF fish 2	117.5 (BCF; 504 h)
BCF other aquatic organisms 1	1100 ppb (BCF)
BCF other aquatic organisms 2	340 - 450 ppb (BCF)
Log Pow	1.4 - 2.82
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Ethanol (64-17-5)</b>	
BCF fish 1	1 (BCF; Other; 72 h; Cyprinus carpio; Static system; Fresh water; Read-across)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Sodium Benzoate (532-32-1)</b>	
Log Pow	0.84
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Propane (74-98-6)</b>	
BCF fish 1	9 - 25 (BCF)
Log Pow	2.28 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Triethanolamine (102-71-6)</b>	
BCF fish 1	< <0.4-<3.9,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 42 days; Cyprinus carpio; Flow-through system; Fresh water; Experimental value
Log Pow	-2.3 - 1.34 (Weight of evidence approach; -1; QSAR)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>IsoButane (75-28-5)</b>	
BCF fish 1	20 - 52 (BCF)
BCF other aquatic organisms 1	20 - 52 (BCF)
Log Pow	2.8 (Experimental value; 20 °C)



# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>IsoButane (75-28-5)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

<b>Diphenylether (101-84-8)</b>	
Surface tension	0.04 N/m (30 °C)

<b>Diethyl Phthalate (84-66-2)</b>	
Surface tension	0.0375 N/m (20 °C)

<b>Ethanol (64-17-5)</b>	
Surface tension	0.022 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Read-across

<b>Propane (74-98-6)</b>	
Surface tension	0.016 N/m (-47 °C)

<b>IsoButane (75-28-5)</b>	
Surface tension	0.014 N/m (-10 °C)

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1950	1950	1950	1950	1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

### - Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP02
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### - Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### - Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

### - Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP02
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

# 250ML AIR FRESHENER REFILL - FRESH LINEN

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*